

**STYRENIC THERMOPLASTIC ELASTOMER COMPOSITION**

Patent number: JP2005089656  
Publication date: 2005-04-07  
Inventor: SHIN GAKUJI  
Applicant: MITSUBISHI CHEM CORP  
Classification:  
- international: C08L53/02; C08L23/00; C08L91/00; C08L53/00;  
C08L23/00; C08L91/00; (IPC1-7): C08L53/02;  
C08L23/00; C08L91/00  
- european:  
Application number: JP20030326759 20030918  
Priority number(s): JP20030326759 20030918

**Report a data error here**

**Abstract of JP2005089656**

**PROBLEM TO BE SOLVED:** To provide a styrenic thermoplastic elastomer composition having good softness, extrusion moldability, surface gloss and scratch resistance.

**SOLUTION:** The styrenic thermoplastic elastomer composition comprises (a) a block copolymer composed of a polymer block of a styrenic compound and a copolymer block of the styrenic compound with a conjugated diene and having  $\geq 50,000$  and  $\leq 100,000$  weight-average molecular weight and/or its hydrogenated block copolymer, (b) an olefinic resin, (c) a softener for hydrocarbon-based rubbers and (d) a block copolymer, composed of a polymer block of a styrenic compound and a polymer block of a conjugated diene and having  $\geq 80,000$  and  $\leq 100,000$  weight-average molecular weight, in which a ratio of 1,2-conjugate occupied in a unit derived from a conjugated diene is  $\geq 20\%$  and  $\leq 50\%$  and/or its hydrogenated block copolymer.

**COPYRIGHT:** (C)2005,JPO&NCIP

.....  
Data supplied from the esp@cenet database - Worldwide